

FloorFolio is now offering more than one type of **EnviroQuiet** LVT to meet the growing needs of this industry. Every project is different, and we aim to provide you with the options you need to get the job done right.

STANDARD

5mm thick | 8mil or 12mil | residential grade

PREMIUM

5mm thick | denser backing | residential

COMMERCIAL

6mm thick | 22mil wear layer | commercial

ASTM F 1700	Vinyl Tile Portion		Class III Type A or B, Pass
ASTM E 662	Smoke Density		Class 1
ASTM E 648	Fire Resistance		Pass
ASTM D 2047	Coefficient of Friction		Pass
ASTM F 970	Static Load		250 PSI
ASTM F 970 <small>*modified</small>	Static Load	STANDARD & PREMIUM	500 PSI
		COMMERCIAL	1000 PSI
ASTM F 925	Chemical Resistance		Pass
ASTM F 410	Wear Layer Thickness	STANDARD & PREMIUM	0.008" or 0.012"
		COMMERCIAL	0.022"
ASTM F 386	Overall Thickness	STANDARD & PREMIUM	5mm (0.197")
		COMMERCIAL	6mm (0.236")

EnviroQuiet[®]

US PATENTS 8640824 & 8893850

EnviroQuiet[®]

US PATENTS 8640824 & 8893850

A Sound Solution.

ONE COST.
ONE INSTALLATION.
ONE SOLUTION.



Exclusively Available at
floorfolio[®]
SALES@FLOORFOLIO.COM
800-671-1124

ONE COST. EnviroQuiet luxury vinyl flooring is manufactured with the sound-reducing underlayment attached, so it can be purchased and installed as one fully integrated product. **ONE INSTALLATION.** The double-patented formula provides an all-in-one, economical flooring solution that can be paired with almost any of our wood or stone visuals. **ONE SOLUTION.**

STANDARD ENVIROQUIET®

US PATENTS 8640824 & 8893850

As it gains popularity throughout the flooring industry, it's clear that this double-patented formula and innovative one-step installation offers valuable time savings and benefits for contractors and end-users alike.

COMPOSITION: Standard EnviroQuiet has an overall thickness of 5mm. Each plank is composed of 2mm thick LVT affixed to a 3mm thick recycled rubber underlayment.

APPLICATION: The 8 mil clear wear layer on the LVT provides longlasting durability in residential areas, making it a great choice for multi-family and student housing. Upgrade to a 12 mil wear layer for increased durability.

STYLE: EnviroQuiet can be paired with almost any of our LVT collections. You can even customize size, color, pattern and texture.

ENVIROQUIET ON DEMAND is a preferred selection of our most popular styles, for which we maintain high volumes of stock, so it's readily available when you need it.



PREMIUM ENVIROQUIET®

US PATENTS 8640824 & 8893850

This premium quality underlayment has a greater density and improved sound performance rating. It's the same great product you know and love, we've just taken it up a notch.



COMPOSITION: Much like the standard version, Premium EnviroQuiet has an overall thickness of 5mm. Each plank is composed of 2mm thick LVT permanently affixed to a 3mm thick rubber underlayment.

APPLICATION: Choice of 8 mil or 12 mil clear wear layer on the 2mm LVT provides longlasting durability in residential areas. The Premium underlayment provides an improved sound barrier and better shock absorption, which is perfect for multi-family housing units that require an added level of privacy and comfort.

STYLE: Premium EnviroQuiet vinyl flooring is manufactured per order, and can be paired with almost any of our wood or stone LVT styles. Custom options are also available.

COMMERCIAL ENVIROQUIET®

US PATENTS 8640824 & 8893850

This commercial grade underlayment has an even greater density than our Premium.

COMPOSITION: With an overall thickness of 6mm, each plank is composed of 3mm thick LVT permanently affixed to 3mm thick, extra dense rubber underlayment.

APPLICATION: The 22 mil clear wear layer on 3mm LVT is a durable solution for high traffic, commercial areas such as hospitals, retail locations, hotels and restaurants.

STYLE: Commercial EnviroQuiet can be manufactured with almost any of our wood and stone LVT styles. Custom options are also available.

