

COMMERCIAL **EnviroQuiet**[®]

US PATENTS 8640824 & 8893850



With an overall thickness of 6mm, each plank is composed of 3mm thick LVT permanently affixed to 3mm thick, extra dense rubber underlayment. The 22 mil clear wear layer on 3mm LVT is a durable, low maintenance solution for high traffic, commercial areas such as hospitals, hotels, restaurants and retail locations.

SALES@FLOORFOLIO.COM | 800-671-1124

ONE COST. ONE INSTALLATION. ONE SOLUTION.

EnviroQuiet luxury vinyl flooring is manufactured with the sound reducing underlayment attached, so it can be purchased and installed as one fully integrated product. The double patented formula provides an all-in-one, economical flooring solution that can be paired with any of our stunning wood or stone visuals.

ASTM F 1700	Solid Vinyl Tile	Class III, Type A or B, Pass
ASTM E 662	Smoke Density	Class 1
ASTM E 648	Fire Resistance	Pass
ASTM D 2047	Coefficient of Friction	Pass
ASTM F 970	Static Load	250 PSI
ASTM F 970 *modified	Static Load	1000 PSI
ASTM F 925	Chemical Resistance	Pass
ASTM F 410	Wear Layer Thickness	0.022"
ASTM F 386	Overall Thickness	6mm (0.236")